



石家庄科昊化工有限公司

SHIJIAZHUANG KEHAO CHEMICAL CO.,LTD

Ningbo office: No. 2412 Taikang Building, Yinzhou District, Ningbo City, Zhejiang China
Factory address: Dongxiu Village, Fangzhi Industrial Zone, Jinzhou City, Hebei Province
Tel: +86 18132059888 E-mail: Ada@xhphmc.com

Technical Data Sheet

Item No.: PVA-2488

Product Overview

PVA-2488 is a partially hydrolyzed, high-viscosity polyvinyl alcohol grade. It provides strong bonding, cohesion and film-forming performance and is especially suitable for construction formulations and adhesives where higher solution viscosity and stronger polymer contribution are required.

Application performance

Desc	Level of improvement
Adhesion	high
Cohesion	high
Film formation	high
Mechanical performance	good
Formulation stability	good

Recommended Applications

Tile adhesive, exterior wall putty, waterproof mortar, repair mortar, high-viscosity construction glue and other dry-mix formulations requiring strong bonding and cohesion.

operating guide

1. Add PVA together with other dry components and disperse uniformly before water addition.
2. The dosage should be determined according to the formulation, target performance and application test.
3. For aqueous preparation, add PVA gradually under agitation and use an appropriate dissolution temperature for the selected grade.

Typical Data

Desc	Range
Appearance	White or slightly yellowish powder
Degree of hydrolysis	87.0-89.0 mol%
Viscosity (4% solution, 20 C)	45.0-55.0 mPa.s
Volatile matter	<=5.0%
Ash content	<=0.5%
pH value	5.0-7.0
Purity	>=93.5%

* The data listed above are typical grade specifications and should be confirmed against the final batch COA.

Packing/Storage&Transportation/Shelf Life

Standard Packing
25kg/Bag
Store in a dry, cool and well-ventilated place. Protect from moisture, heat and direct sunlight.

Shelf Life

Keep in dry and cool conditions for at least 12 months. If stored beyond the stated shelf life, the product should be tested before use.

product safety

Handle in accordance with good industrial hygiene and safety practice. Avoid dust generation and unnecessary inhalation.

For further information, see the Product Safety Data Sheet.